



TransPro® 80/100

WALK GREENSMOWER TRAILERS

FEATURES

TransPro 80

- Safely transport 1 walk greens mower
- Rail ramp simplifies operation and reduces loading time by 50% – no need to mount mower transport wheels
- Large trailer tires to cushion ride and help protect mower during transport
- Rubber mat protects greens mower front rollers during transport, helping keep mower adjustments intact
- Open design allows servicing and washdown while mower is on the trailer
- Quick-lock device secures mower to the trailer for safe transport



TransPro 80

TransPro 100

- Safely transport 1 or 2 walk greens mowers
- Rail ramp simplifies operation and reduces loading time by 50% – no need to mount mower transport wheels
- Large trailer tires to cushion ride and help protect mower during transport
- Rubber mat protects greens mower front rollers during transport, helping keep mower adjustments intact
- Quick-lock device secures mower to the trailer for safe transport
- Can also be used as a utility trailer



TransPro 100

Safely and easily transport one or two walk greensmowers.

Toro® TransPro® trailers safely and easily transport walk greens mowers to and from the green. The unique design protects your greens mower investment and keeps adjustments intact. The TransPro 80 accommodates a single Greensmaster® with a Flat Ramp or Rail Ramp Kit. For additional time and productivity gains, transport two walk greens mowers (excluding the Greensmaster 1600 and Greensmaster 1026) with the TransPro 100.



TransPro® 80 & 100

Safely and easily transports one or two walk greensmowers to and from the green.



	TRANSPRO 80, MODEL 04238*	TRANSPRO 100, MODEL 04240*
LOAD CAPACITY	400 lbs. (181.6 kg) including weight of trailer.	800 lbs. (363 kg) including weight of trailer.
SUSPENSION	Large low pressure tires (20 x 10-8).	
TRANSPORT SPEED	Maximum of 15 mph (24 km/h).	
RAMP	Quick latch to secure loading ramp during transport. Rubber mats to protect front roller. Flat Ramp Kit or Rail or Ramp Kit required.	Quick latch to secure loading ramp during transport. Rubber to protect front roller and provide safe surface during loading unloading of Greensmaster. High Rail Ramp Kit optional.
HITCH	Pin type hitch is standard; tongue is 2.5" (6.4 cm) wide and adjustable in length (will accept standard ball hitch).	Pin type hitch is standard; tongue is 2" (5 cm) wide and adjustable in length (will accept standard ball hitch).
TOWING	Designed to tow behind a utility vehicle; tongue height 7"-13" (18-33 cm); maximum tongue load 55 lbs. (25 kg). Incorporates a tongue stand and tongue lift handle.	
BED		Hold down bails fold around mower tires to during transport. Drain holes in trailer bed for greensmower on trailer, allowing water and trailer floor.
FINISH	Rust/corrosion-resistant paint.	
AXLES	Heavy-duty stub. Greaseable.	
DIMENSIONS	Height: 19" (48.3 cm) Width: 62" (157.5 cm) Length: 81" (205.7 cm)	Height: 36" (91.4 cm) Width: 60.5" (153.7 cm) Length: 101" (256.5 cm)
	Easily adjustable to fit all Toro walk greensmowers.	For 21" mowers with transport tires (standard), conversion kits available for 18" mowers. Rail kits available for both 18" and 21" mowers (not recommended for Greensmaster® 1600).

TRANSPRO 80 ACCESSORIES	TRANSPRO 100 ACCESSORIES
04245 Flat Ramp Kit	138-5011 Rail Ramp Conversion Kit (RoHS Compliant)
04247 Rail Ramp Kit	136-8567 18" Transport Wheel Conversion Kit
107-8188 Hitch Kit	110-7345 18" Rail Conversion Kit
136-7287 Extended Axle for Rail Ramp Using 04648 Groomer	139-6470 Greensmaster 1018 Wheel Retention Kit
	139-2683 Greensmaster 1021 Wheel Retention Kit

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.

